



Manual call point, WCP5A-RP02SF-E010-01, isolated, flex element

FFS06423668E

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Manual call point
Colour tint	Red RAL 3001)

Complementary

Material	PC/ABS
Control type	Resettable
[Ue] rated operational voltage	30 V DC maximum
Current consumption	500 µA 24 V DC standby 7.6 mA 24 V DC alarm
Cable cross section	0,5...2,5 mm² cable
Height	93 mm
Width	97,5 mm
Depth	71 mm
Product weight	240 g

Environment

IP degree of protection	IP67D
Ambient air temperature for operation	−10...55 °C
Standards	EN 54-11
Product certifications	LPCB
Relative humidity	0...95 % non-condensing

Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	370,0 g
Pakk 1 kõrgus	11,0 cm
Pakk 1 laius	10,0 cm
Pakk 1 pikkus	10,0 cm

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.