



Fire detection panel, Esmi Fire detection panels, FX 3NET, for Estonia

FFS00703602EE

Main

Range of product	Esmi fire detection panels
Product or component type	Control panel
Number of batteries	2 x 12 V 17 Ah
Colour	Cover light blue/grey NCS S 4020-R80B) Collar dark blue/grey NCS S 5020-R80B) Frame dark grey NCS S 7502-B)
Maximum allowed current consumption	1.0 A 24 V DC standby 4.8 A 24 V DC alarm

Complementary

Mains supply power	165 VA
Mains supply voltage	230 V AC +/- 10 % 50...60 Hz
Operating voltage range	19...30 V DC
Device composition	cover plastic frame sheet steel/plastic back frame sheet steel
Height	578,0 mm
Width	425,0 mm
Depth	130,0 mm
Product weight	11,0 kg without batteries
Addressable loop controller	ALC/SLC
Number of loops	8 addressable
Number of addresses	0...159 addressable detectors and call points for SLC 0...159 other modules for SLC 0...126 addressable devices for ALC
Optional circuit board slots	5 optional circuit board
Product compatibility	Fireman's panel FMPX/FMP2 Protocol repeater REPX/REPX-OB Delay alarm panel DAPX/DAP2 Logical controller MCOX/MCOX-OB LED panels for fire zones ZLPX

Environment

Standards	EN 54-2 EN 54-4
Relative humidity	0...95 % non-condensing

Ambient air temperature for operation	5...40 °C
Ambient air temperature for storage	0...50 °C
IP degree of protection	IP30

Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	10760,0 g
Pakk 1 kõrgus	16,5 cm
Pakk 1 laius	47,0 cm
Pakk 1 pikkus	67,0 cm

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Contractual warranty

Garantii	24 months
----------	-----------