

Product data sheet

Specifications



Sounder control module, EMI-301/S, with isolator

FFS06727351

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Sounder control unit

Complementary

[Ue] rated operational voltage	17...28 V DC
Current consumption	1.95 mA at 24 V DC standby 2.6 mA at 24 V DC power-up surge 1.7 mA at 24 V DC sounders operated
Load current	1 A at 24 V DC continuous load 3 A at 24 V DC for switch
Colour	White
Provided equipment	Isolator
Height	90 mm
Width	150 mm
Depth	48 mm
Net weight	240 g

Environment

Standards	EN 54-17 EN 54-18
Product certifications	LPCB CPD
IP degree of protection	IP54
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-20...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5 cm
Package 1 width	12.5 cm

Package 1 Length	12.5 cm
------------------	---------

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information