



Optical smoke detector, Intellia EDI-20

FFS06720220

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Optical smoke detector

Complementary

[Ue] rated operational voltage	17...28 V DC polarity insensitive
Current consumption	300 µA 24 V DC standby 3.5 mA 24 V DC alarm 1 mA 24 V DC power-up surge 5 mA 24 V DC remote LED
Material	Body PC (polycarbonate) FR Terminal nickel plated stainless steel
Local signalling	2 LED red) alarm
Output type	Remote LED optional
Colour	white
Diameter	100 mm
Height	42 mm
Product weight	105 g

Environment

Standards	EN 54-7
Product certifications	CPR LPCB
IP degree of protection	IP44
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-40...80 °C

Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	250,0 g

Pakk 1 kõrgus	5,0 cm
Pakk 1 laius	12,5 cm
Pakk 1 pikkus	12,5 cm

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.
Keskkonnaalane avaldus	Toote keskkonnaprofiil
Ringlusprofiil	Kasutuselt kõrvaldamise teave