

Product data sheet

Specifications



Twin switch monitor, Essentia EME211-I

FFS06720317

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Switch monitor

Complementary

[Ue] rated operational voltage	17...35 V DC
Current consumption	500 µA at 24 V DC standby 900 µA at 24 V DC power-up surge 2 mA at 24 V DC maximum LED on 500 µA at 24 V DC maximum LED disabled
Colour	White
Local signalling	LED flashing green for polling LED yellow for isolation LED yellow for input fault LED red for input active
Height	60 mm
Width	150 mm
Depth	90 mm
Net weight	273 g

Environment

Standards	EN 54-17 EN 54-18
Product certifications	LPCB CPR
IP degree of protection	IP52
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	310.0 g
Package 1 Height	10 cm
Package 1 width	16 cm

Package 1 Length	9 cm
------------------	------

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information