

Product data sheet

Specifications



Manual call point, EPP-22A, waterproof, with isolator

FFS06723701

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Manual call point
Colour tint	Red

Complementary

Control type	Resettable
[Ue] rated operational voltage	17...28 V DC
Signalling function	Alarm status LED red Short circuit LED yellow
Type of setting	7-segment DIL switch: address setting
Current consumption	100 µA standby 1 mA power-up surge 1s typical 4 mA alarm LED on
Height	114 mm
Width	114 mm
Depth	74 mm
Product weight	325 g

Environment

IP degree of protection	IP56 with IP67 rated electronics enclosure
Ambient air temperature for operation	-30...70 °C
Standards	EN 54-11 EN 54-17
Product certifications	CPR
Relative humidity	0...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 width	12.5 cm
Package 1 Length	12.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information