

Overdoor Light c/w Sounder

Part No. NC806CS



Overview

- Provides audible and visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series
- Indicates Standard calls via a constant tone/constant red light and Emergency calls via a pulsing tone/pulsing red light.
- Dual red LEDs and triangular diffuser make it highly visible from a distance.
- Mounts on a standard UK 25mm single gang flush or surface back box.
- Can also be used as an 'area indicator' at corridor junctions, staff workstations, etc.
- Finished in tough, durable ABS plastic.
- Also available as part of the NC951 Accessible Toilet Alarm kit.
- Stainless steel version also available.



More Information

Technical Specifications

Quiescent current 0mA (none).

Alarm current Determined by the type of control equipment and number / type of field devices connected to the system. Indicators Dual ultra-bright red Alarm LEDs (lit constantly for standard calls, intermittently for emergency calls).

Controls None (the device is controlled by the master calling device it is connected to).



T 01942 322744

E sales@c-tec.co.uk

W www.c-tec.com



















Connections 1 (Signal); -Ve (Negative); +Ve (Positive).

Onboard Sounder Yes. Sounds constantly for standard calls, intermittently for emergency calls.

Onboard Infrared Receiver

87~W~x~87~H~x~68~D~mm. Mounts on a UK 25mm single gang back box. Product dimensions (mm)

Construction & finish IP Rating IP41. Weight 52g.

Operating conditions/temperature -5 $^{\circ}$ C to +40 $^{\circ}$ C. Max. relative humidity 95% non-condensing.

















