



Main

Range of product	Esmi addressable components for ELC range
Product or component type	Output module

Complementary

[Ue] rated operational voltage	15...32 V DC
Current consumption	270 µA 27 V DC standby 3.6 mA
Load current	0,75 A 28 V DC relay output 0,5 A 120 V AC relay output
[Us] rated supply voltage	27 V 24...30 V)DC
Colour	Grey
Material	PS (polystyrene)
Provided equipment	Isolator
Cable cross section	0,4...2,5 Mm ²
Mounting location	Indoor Outdoor
Length	176 Mm
Height	57 Mm
Width	126 Mm
Net weight	320 G

Environment

Standards	EN 54-17 EN 54-18
Product certifications	CPR
IP degree of protection	IP55
Relative humidity	0...96 % non-condensing
Ambient air temperature for operation	-10...60 °C

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	6 Cm
Pakendi laius 1	12,8 Cm
Pakendi pikkus 1	18,2 Cm
Pakendi kaal 1	391 G

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Product Life Status : **Commercialised**