



Main

Range of product	Esmi addressable components for ELC range
Product or component type	Programming tool

Complementary

[Ue] rated operational voltage	4.2...8 V DC
Current consumption	26...30 mA 6 V DC standby 20...24 mA 6 V DC when backlight is OFF 55...65 mA 6 V DC with communication
Material	ABS (acrylonitrile butadiene-styrene)
Colour	White
Number of addresses	1...250
Number of batteries	4 AA 1,5 V
Language	English Bulgarian Russian Turkish
Height	65 Mm
Width	102 Mm
Length	255 Mm
Net weight	260 G

Environment

Relative humidity	0...93 % non-condensing
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-20...70 °C

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	7,5 Cm
Pakendi laius 1	15,5 Cm
Pakendi pikkus 1	25,5 Cm
Pakendi kaal 1	680 G

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Product Life Status : **Commercialised**