



Main

Range of product	Esmi addressable components for ELC range
Product or component type	Manual call point
Colour tint	Red

Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Control type	Resettable
[Ue] rated operational voltage	15...32 V DC
Current consumption	160 µA 27 V DC standby 3 mA alarm
Cable cross section	0,4...2,0 Mm ² cable
Height	90 Mm
Mounting location	Indoor
Width	90 Mm
Depth	57 Mm
Product weight	175 G

Environment

IP degree of protection	IP40
Ambient air temperature for operation	-10...60 °C
Standards	EN 54-11 EN 54-17
Product certifications	CPR
Relative humidity	0...96 % non-condensing

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	6 Cm
Pakendi laius 1	9,3 Cm
Pakendi pikkus 1	9,3 Cm
Pakendi kaal 1	174 G

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Product Life Status : Commercialised
