



Main

Range of product	Esmi addressable components for ELC range
Product or component type	Smoke detector

Complementary

[Ue] rated operational voltage	15...32 V DC 27 V DC nominal
Current consumption	310 µA 27 V DC standby 6.5 mA alarm
Provided equipment	Isolator
Output type	Alarm output 7.5 V 7.5 mA
Cable cross section	0,4...2,0 Mm ²
Diameter	103 Mm
Level	High Normal Middle Low
Height	48,3 Mm with mounting base)
Product weight	94,5 G without mounting base

Environment

Standards	EN 54-7 EN 54-17
Product certifications	CPR
IP degree of protection	IP30
Relative humidity	0...96 % non-condensing
Ambient air temperature for operation	-10...60 °C

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	10,8 Cm
Pakendi laius 1	10,8 Cm
Pakendi pikkus 1	36,5 Cm
Pakendi kaal 1	104 G

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Product Life Status : Commercialised
