



Key Features

Fast Installation



Allows Airflow around the LHD Cable



Quick Release and Insert



Nylon Construction



Low Smoke Zero Halogen



Overview

The FyreLine Quick Release “T” clip is designed to provide clear airflow around linear heat detection sensing cable to ensure maximum sensitivity and operation. The “T” clip simplifies the installation and maintenance of linear heat sensing cable; its quick-release design enables fast installation of cables which can also be temporarily removed quickly and easily for routine maintenance or repairs, without having to remove the clip.

The sensitivity of a linear Heat Detection System can be affected if long lengths of the cable are in physical contact with any surfaces. Quick Release “T” clips, fixed at regular intervals allow air to flow freely around the cable, increasing sensitivity. This also ensures that the cable is fully supported and that the risk of mechanical damage is mitigated.

The FyreLine Quick Release “T” Clip is compatible with FyreLine systems as well as existing Proline TH linear heat detection systems. It also provides a direct alternative to the PR-001 “T” Clip.

For use in installations that accept plastic fixings only.

Tech Specs

Weight	2.5g
Material	Nylon
Melt Temperature	220°C
Flammability	To UL 94
Maximum Cable Size	4mm ²

Ordering Information

Part Number	Description
18-370	Quick Release Plastic ‘T’ Clip, 100 Pack