

# F-1000BTWP

SPEAKER SYSTEM

The F-1000 Series Speaker are compact two-way speaker systems designed for high efficiency, wide range, and high power input handling capability. These speaker systems can be installed in a manner ideal for the location and intended application. The F-1000BTWP features a water-proof design (splash-proof type meeting IPX4 standard), so that it can be permanently installed outdoors.



Article number:F-1000BTWP  
Alternative products: F-1000B, F-1000BT,  
F-1000W, F-1000WT, F-1000WTWP

## Specifications

Sensitivity (1#W, 1#m)	87 dB at installation in 1/2 free sound field
Frequency response	85 Hz - 20 kHz (-10 dB)
Crossover frequency	5 kHz
Rated input (high impedance)	15 W
Tappings	100 V : 670 Ω (15 W) / 2 kΩ (5 W) / 3.3 kΩ (3 W) / 10 kΩ (1 W) 70 V : 330 Ω (15 W) / 670 Ω (7.5 W) / 2 kΩ (2.5 W) / 3.3 kΩ (1.5 W) / 10 kΩ (0.5 W)
Speaker component	Low: 10 cm cone-type, High: 2.5 cm balanced dome-type
Finish	HIPS resin, black (RAL 9011 or equivalent),
Operating temperature	-10 °C to +50 °C ( 14 °F to 122 °F)

# F-1000BTWP

SPEAKER SYSTEM

Appearance

