
LinkSide

Fiber Optic Patch Panel 24xSC duplex 19" 1U, rack mount

Product code: 490131

Fiber Optic Patch Panel with removable tray for mounting in cabinets and 19" racks, for terminating fiber optic transmission links with pigtails.

- 1U height, for mounting in a 19" rack,24 SC duplex ports
- designed to perform main and intermediate fiber distribution points
- panel design in the form of a pull-out drawer enables convenient assembly of connectors and service
- exchangeable front plate with numbering of ports for mounting adapters in versions: SC simplex, SC duplex, ST, FC, LC, E2000
- color RAL 9005 (black)
- five holes in the back
- adjustable mounting ears
- special handles enable mounting of 4 optical fiber cassettes (possibility of removing the cassette retaining screw)
- steel panel housing powder coated
- the set includes fastening elements, cable glands and cable ties splice cassette is not included











Dimensions				
Height	44 mm			
Width	435 mm			
Depth	245 mm			
Tray	235 mm (tray depth after extension)			

LinkSide



Electrical Properties:

Max. conductor resistance	93.8Ω/km @20°C		
Max. mutual capacitance	5.6nF/100m		
Max. resistance unbalance	5%		
Max. capacitance unbalance	330 pF/100m		

Frequency	Attenuation	Return Loss	NEXT	P.S NEXT	FEXT	P.S ELNEXT	
MHz	Min.dB/100m	dB	Min.dB/100m	Min.dB/100m	Min.dB/100m	Min.dB/100m	
1	2.0	74.3	72.3	72.3	67.8	64.8	
4	3.8	65.3	63.3	61.5	55.8	52.8	
8	5.3	60.8	58.8	55.4	49.7	46.7	
10	6.0	59.3	57.3	53.3	47.8	44.8	
16	7.6	56.2	54.2	48.6	43.7	40.7	
20	8.5	54.8	52.8	46.2	41.8	38.8	
25	9.5	53.3	51.3	43.7	39.8	36.8	
31.25	10.7	51.9	49.9	41.1	37.9	34.9	
62.5	15.4	47.4	45.4	31.7	31.9	28.9	
100	19.8	44.3	42.3	24.1	27.8	24.8	
200	29.0	39.8	37.8	10.0	21.8	18.8	
250	32.8	38.3	36.3	4.6	19.8	16.8	

Electrical Performance

