



## Detector base beacon sounder, BSS-PR-I33, with isolator

FFS06711723

### Main

|                           |                                           |
|---------------------------|-------------------------------------------|
| Range of product          | Esmi addressable components for SLC range |
| Product or component type | Mounting base                             |

### Complementary

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Product destination            | Audible visual alarm                                 |
| Colour tint                    | Body pure white<br>Lens red                          |
| [Ue] rated operational voltage | 15...29 V DC                                         |
| Current consumption            | 225 µA standby<br>13.9 mA alarm                      |
| Signalling type                | 32 tones alarm                                       |
| Acoustic level                 | 91...97 dBA 1 m                                      |
| Type of setting                | Volume low<br>Volume medium<br>Volume high           |
| Local signalling               | LED red flashing alarm                               |
| Cable cross section            | 1,5...2,5 mm²                                        |
| Device mounting                | Base mounting low profile<br>Base mounting deep base |
| Diameter                       | 121 mm                                               |
| Height                         | 64 mm low profile)<br>119 mm deep base)              |
| Net weight                     | 200 g                                                |

### Environment

|                                       |                                                    |
|---------------------------------------|----------------------------------------------------|
| Standards                             | EN 54-3<br>EN 54-17                                |
| Product certifications                | LPCB<br>CPR                                        |
| IP degree of protection               | IP21C with low profile base<br>IP44 with deep base |
| Relative humidity                     | 0...95 % non-condensing                            |
| Ambient air temperature for operation | -25...70 °C                                        |

Suurim lubatud võrreldavate toodete arv on täis. Avage jaotis Võrreige tooteid #LINK# ja kustutage jätkamiseks mõni toode

Pakke osad

|                   |         |
|-------------------|---------|
| Osa tüüp pakil 1  | PCE     |
| Osade arv pakis 1 | 1       |
| Pakk 1 kaal       | 232,0 g |
| Pakk 1 kõrgus     | 6,0 cm  |
| Pakk 1 laius      | 12,5 cm |
| Pakk 1 pikkus     | 12,5 cm |

Offer Sustainability

|                         |                                                                                                                |
|-------------------------|----------------------------------------------------------------------------------------------------------------|
| REACH-määrus            | <a href="#">REACH-deklaratsioon</a>                                                                            |
| ELi RoHS direktiiv      | Vastavus<br><a href="#">ELi RoHS deklaratsioon</a>                                                             |
| Elavhõbedavaba          | Jah                                                                                                            |
| RoHS eranditeave        | <a href="#">Jah</a>                                                                                            |
| Hiina EoHS regulatsioon | <a href="#">Hiina RoHS deklaratsioon</a><br>Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks. |